





The recycling collector 1000 SRS is used for medium and large parts: For cleaning bicycles or motorbikes up to parts weighing 10 tons which are lifted onto the collector with a crane or a forklift. These can then be cleaned resp. degreased using a low pressure hot cleaning machine from ph-cleantec. The dirt water can be reused.

The standard collector has the size of standard euro-palette (1200 x 800 mm), other sizes up to 10m² or above can be delivered upon request. The payload amounts to 1 to per m². The collector is equipped with a splash guard by default, and be upgraded with additional features such as wheels, an inclined base plate, or support columns up to 88 cm working height.

Collect & recycle				
dirt water for large				
parts				

√	Size of standard euro-palette up to 10 m²; 1m² ≈ 1 t
✓	Ideal for large parts with crane or forklift
✓	Collects and recycles dirt water


Workshops for vehicles, bicycles, and motorbikes

\checkmark	Ideal for companies with environmental conscience
√	Ideal for bicycles and motorbikes (with splash protection)
√	Usage of cleaning agent in circulatory system (saves costs)



Technical Data 1000 SRS

- Automatic recycling of dirt water and return into lov pressure hot cleaning machine
- Any size from euro-palette to 10m²
- Load capacity 1 ton per square meter
- With splash protection, 1m high
- With discharge tap to change water
- Can be picked up with forklift



• Upon request with inclined base plate or higher working height up to 88 cm

Technical Data	1000 SRS
Dimensions	Standard size 1200 x 800 x 400 mm (euro-palette) Other sizes up to 10m ² according to specification
Load capacity	~ 1 ton per square meter
Filling capacity	200 liter (standard collector)
Discharge head	Up to 4 meters
Discharge volume	~ 8-10 liters / minute
Water recycling	100 μm filter + 25 μm filter
Type of current	1P-N-PE / 230V / 50Hz / 16A
Power capacity	0.35 KW
Splash guard	Standard
Connector cable	7.5 meters
Hoses	Return hose 3 meters
Wheels, push handle, slosh brake	Upon request
Inclined floor board	Upon request
Higher working level (up to 88 cm)	Upon request

Subject to technical modifications. As of August 13, 2021.