ph-cleantec
CLEARLY CLEAN RESULTS

1000 SRS

Heavy Duty Collector



1000 SRS
custom-made collector

The recycling collector 1000 SRS is used for medium and large parts: For cleaning bicycles or motorbikes up to parts weighing 10 tons which are lifted onto the collector with a crane or forklift. These can then be cleaned resp. degreased using a low pressure hot cleaning machine from ph-cleantec. The dirt water can be reused.

The hot-dip galvanised steel collector has the size of standard euro-palette (1200 x 800 mm), other sizes up to 10m² or above can be delivered upon request. The payload amounts to 1 to per m². The collector is equipped with a splash guard on three sides, and be upgraded with additional features such as wheels, an inclined base plate, or support columns up to 88 cm working height.

Collect & recycle dirt water for large parts	✓ Size of standard euro-palette up to 10 m²; 1m² ≈ 1 t ✓ Ideal for large parts with crane or forklift ✓ Collects and recycles dirt water
Workshops for vehicles, bicycles, and motorbikes	✓ Ideal for companies with environmental conscience ✓ Ideal for bicycles and motorbikes (with splash protection) ✓ Usage of cleaning agent in circulatory system (saves costs)

ph-cleantec
CLEARLY CLEAN RESULTS

Technical Data 1000 SRS

- Automatic recycling of dirt water and return into low pressure hot cleaning machine
- Any size from euro-palette to 10m²
- Load capacity 1 ton per square meter
- With splash protection, 1m high
- With discharge tap to change water
- Can be picked up with forklift
- Upon request mobile with push handle, wheels, and slosh brake
- Upon request with inclined base plate or higher working height up to 88 cm



1000 SRS standard collector combined with 1000 SRE

Technical Data	1000 SRS
Dimensions l x w x h	1200 x 800 (Euro-palette) x 1350 mm h : 100 mm underdrive forklift h: 260 mm collector h: 1000 mm splash protection Other sizes up to 10m² according to specification
Load capacity	~ 1 ton per square meter with evenly distributed load
Material	Hot-dip galvanized steel
Splash guard	3 sided, height 1000 mm
Filling capacity	Up to 200 litres, adjustable
Discharge volume	~ 20 litres / minute
Discharge head	Up to 4 meters
Pressure	Max. 2 bars
Type of current	1P-N-PE / 230V / 50Hz / 16A
Power capacity	0.34 KW
Noise level	< 70 Dba
Filtration	100 µm filter with removable sieve + 25 µm filter
Connector cable	7.5 meters
Connection hose	3 meters
Wheels, push handle	Upon request
Inclined floor board, slosh brake	Upon request
Higher working level (up to 88 cm)	Upon request

Subject to technical modifications. As of 01.08.2025.